



TEXIMPLAST

Teximplast LLP
26-28 Bedford Row
London WC1R 4HE
United Kingdom
E-mail: info@teximplast.com



PET STRECH BLOW MOLDING MACHINE

SEMIAUTOMAT



General characteristics

capacity	500-600 max BPH 2l
mould	2 cavity
bottle vol.	0,2-2 l
bottle height	330 mm
bottle diameter	100 mm
outer neck diameter	28 mm
length of preform	155 mm
Heating chamber	
heater type	infrared
heater lamps number	4
adjust zone number	4
Clamping unit	
clamping	pneumatic-mechanic
platen stroke	/
max. mould size	300x230x330 mm
mould thickness	115 mm
Stretching	
max. stretching stroke	330 mm
distance bet. stretching rods	160 mm
Air supply	
operating air pressure	7 bar
operating air consumption	166 l/min
blowing air pressure	15 bar
Cooling	
power	0.7 kw
heat exchange	1.5 kcal
El. power	
operating power	0.5 kw
heater power	7.75 kw
Dimension	
weight	800 kg
Machine + preform cabine	250x120x170 cm
Air compressor	
capacity	1100 l/min
pressure	15 bar
tank volume	500 lit
power	7.9 kw
weight	150 kg
dimensions	200x75x150 cm

